615 242 2221;

Dec-24-03 11:09AM;

Sent By: Waddey & Patterson;

Page 3

APPLICATION NO. 10/074,720 DOCKET NO. N0514

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-25 (canceled)

Claim 26 (original): A graphite body having a substantially homogenous distribution of carbon fibers dispersed within said graphite body as substantially single mono-filaments of a random orientation, said carbon fibers present in an amount of about 1.5 wt.% to about 3.0 wt.% based on a weight of said graphite body

Claim 27 (Previously presented): A graphite body having a longitudinal coefficient of thermal expansion of about -0.5 x 10-6/°C to about 0.10 x 10-6/°C as measured from about 25 to about 200°C and substantially homogenous distribution of carbon fibers dispersed within said graphite body as substantially single non-filaments of random orientation, said carbon fibers present in an amount of about 1.5 wt.% to about 3.0 wt.% based on a weight of said graphite body.

Claim 28 (original): A graphite body having a substantially homogenous distribution of carbon fibers dispersed within said graphite body as substantially

APPLICATION NO. 10/073,720 DOCKET NO. N9514

Dec-24-03 11:10AM;

single mono-filaments of a random orientation, said carbon fibers present in an amount of about 1.5 wt.% based on a weight of said graphite body.

Claim 29 (original):

A graphite body produced by a method of:

- (a) providing a binder comprising an admixture of pitch having about 0.5 to about 10.0 wt.% of carbon fibers based on a weight of said pitch, substantially homogeneously dispersed within said pitch as substantially single mono-filaments of a random orientation;
 - (b) providing a filler;
- (c) mixing said binder and said filler to produce a binder-filler mix having a substantially homogenous dispersion of carbon fibers which are randomly oriented throughout;
 - (d) extruding said binder-filler mix to form a carbon body;
 - (e) carbonizing said carbon body;
- (f) graphitizing said carbon body to produce said graphite body having about 1.5 to about 3.0 wt.% carbon fibers based on a weight of said graphite body, said fibers dispersed throughout said graphite body as substantially single mono-filaments of a random orientation.

Claim 30 (original):

A graphite body produced by a method of:

(a) mixing a binder comprising an admixture of pitch having a viscosity of about 0.1 to about 5 poise at a temperature of about 260 to about 140°C and about 0.5

APPLICATION NO. 10/073,720 DOCKET NO. N9514

to about 10.0 wt.% of carbon fibers based on a weight of said pitch, said fibers substantially homogeneously dispersed within said pitch as substantially single monofilaments of a random orientation, with a coke filler to form a binder-filler mix;

- (b) extruding said binder-filler mix to form a carbon body;
- (c) carbonizing said carbon body;
- (d) graphitizing said carbon body to produce said graphite body having about 1.5 to about 3.0 wt.% carbon fibers based on a weight of said graphite body, said fibers dispersed throughout said graphite body as substantially single mono-filaments of a random orientation.

Claim 31-33 (canceled)

Claim 34 (previously presented): The graphite body according to claim 26 wherein a length of said carbon fiber comprises about 5 mm to about 40 mm.

Claim 35 (previously presented): The graphite body according to claim 27 wherein a diameter of said carbon fibers comprises about 5 μ m to about 30 μ m.

Claim 36 (previously presented): The graphite body according to claim 27 wherein a length of said carbon fiber comprises about 5 mm to about 40 mm.

Sent By: Waddey & Patterson;

Dec-24-03 11:10AM;

APPLICATION NO. 10/073,720 DOCKET NO. N9514

Claim 37 (previously presented): The graphite body according to claim 28 wherein a diameter of said carbon fibers comprises about 5 μm to about 30 μm .

Claim 38 (previously presented): The graphite body according to claim 26 having a longitudinal coefficient of thermal expansion of about -0.5 x 10 6/°C to less than 0.14 x 10-6/°C as measured from about 25 to about 200°C.

Claim 39 (previously presented): The graphite body according to claim 26 wherein a tensile strength of said carbon fiber comprises greater than about 100,000 psi.

Claim 40 (previously presented): The graphite body according to claim 27 wherein a tensile strength of said carbon fiber comprises greater than about 100,000 psi.

Claim 41 (previously presented): The graphite body according to claim 28 wherein a tensile strength of said carbon fiber comprises greater than about 100,000 psi.